



Model:S3178

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L125*W61*H22mm



Model: S3472H

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L280*W40*H13mm



Model:S4032

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L100*W65*H15mm



UL CE BHMA
Hotel Locks

Hotel Locks



Model:S3076

Material: Stainless Steel & High strength zinc alloy
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L62*W62*H12mm



Model:S3479A

Material: Stainless Steel & High strength zinc alloy
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L60*W60*H12mm



Model:S3474

Material: Stainless Steel & High strength zinc alloy
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L52*W52*H12mm



Model:E3092A

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L295*W76*H17mm



Model:E3064P

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L280*W40*H13mm



Model:E3042

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L290*W60*H15mm



UL CE BHMA
Hotel Locks

Hotel Locks



Model:E3441

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L290*W60*H15mm



Model:E4031

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L280*W75*H22mm



Model:E4441

Material: Stainless Steel, Moisture Proof, Fire Retardant
Unlocking record: 1680PCS
Power Consumption: Static Load < 30μA, Dynamic Load < 200 mA
Working Humidity: 20%-90% Working Temperature: -20°C~60°C
Dimension of External Panel: L285*W75*H16mm



Smart Hotel & Smart Home
Professional Innovative

